



*Picture for illustrative purposes only

DESIGN SPECIFICATIONS


- ✓ High quality, reliable and complete power unit
- ✓ Compact design
- ✓ Easy start and maintenance
- ✓ Fully tested for load, controls and safety shutdown functions
- ✓ Fully engineered with a range of optional extras and accessories.

240V 50 Hz	Generating Set Model		JSPSP 45
Power Factor 1.0	Prime	kVA	45
		kW	45
	Standby	kVA	50
		kW	50

Prime: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046.
Standby: Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046, BS 5514.

TECHNICAL DATA*			
Engine Model	Perkins 1103A-33TG2	Alternator	Mecc Alte
Number of Cylinders	3 in-line	Heat Rejection to Exhaust (Max)	30.5 kW
Cubic Capacity	3.30 litre	Heat Rejection to Cooling System (Max)	30.0 kW
Aspiration	Turbocharged	Exhaust Temperature (Max)	537 deg C
Engine Speed (RPM)	1500 rpm	Combustion Air Flow (Max)	3.9 cu m/min
Frequency	50 Hz	Fuel Tank Capacity	220 litre
Amperage	187 amps	Fuel Consumption at Full Prime Rating	10.7 litre per hour

DIMENSIONS*	
Length (A)	2,385 mm
Width (B)	1,100 mm
Height (C)	1,643 mm
Total Height of exhaust rain cap (D)	1,752 mm
Max Horizontal projection of end door (E)	750 mm
Max Horizontal projection of side door (F)	1,085 mm
WEIGHT*	
Dry Weight (For Shipping)	1,397 kg



SOUND LEVELS*			
Load	15m	7m	1m
100%	58.0 dB(A)	64.0 dB(A)	73.3 dB(A)
75%	57.1 dB(A)	63.1 dB(A)	73.1 dB(A)

FEATURES*	Manual Start, Main Power Set		Automatic Start, Standby Set	
	Standard	Optional	Standard	Optional
Sound Attenuated, Weatherproof Canopy	✓		✓	
Base Fuel Tank	✓		✓	
DEFRA Bunded Base Fuel Tank (Standard on UK Models)		✓		✓
Oil, Fuel & Air Filters	✓		✓	
Coolant Water Heater			✓	
Lube Oil Drain	✓		✓	
Vibration isolated Control Panel	✓		✓	
Manual Control Panel	✓			
Auto Start Control Panel			✓	
Integral 5A Battery Charger			✓	
Automatic Transfer Panel				✓
12 Months International Warranty	✓		✓	
Output Circuit Breaker	✓		✓	
CE Certification (Standard on UK / EU Models)		✓		✓
Service / Maintenance Contracts/ NetBiter Remote Monitoring		✓		✓

*Specifications subject to change without notice