



*Picture for illustrative purposes only

DESIGN SPECIFICATIONS

- ✓ High quality, reliable and complete power unit
- ✓ Compact design
- ✓ Easy start and maintenance
- ✓ Fully tested for load, controls and safety shutdown functions
- ✓ Warranted for B100 Bio Diesel at EN14214 Standard
- ✓ List of Optional Extras

| 400/230V 50 Hz | Generating Set Model | | JSP BD 200 |
|---------------------|----------------------|-----|------------|
| Power Factor 0.8 | Prime | kVA | 200 |
| | | kW | 160 |
| | Standby | kVA | 220 |
| | | kW | 176 |

Prime: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046.
Standby: Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046, BS 5514.

TECHNICAL DATA*

| | | | |
|---------------------|-----------------------|--|---------------------|
| Engine Model | Sisu Diesel 634 DSRAG | Alternator | Newage Stamford |
| Number of Cylinders | 6 in-line | Heat Rejection to Exhaust (Max) | 165.0 kW |
| Cubic Capacity | 7.40 litre | Heat Rejection to Cooling System (Max) | 102.0 kW |
| Aspiration | Turbocharged | Exhaust Temperature (Max) | 565 deg C |
| Engine Speed (RPM) | 1500 rpm | Combustion Air Flow (Max) | 9.4 cu m / min |
| Frequency | 50 Hz | Fuel Tank Capacity‡ | 400 litre |
| Amperage | 277 amp per phase | Fuel Consumption at Full Prime Rating | 44.1 litre per hour |

DIMENSIONS*

| | |
|--|----------|
| Length (A) | 3,700 mm |
| Width (B) | 1,150 mm |
| Height (C) | 1,975 mm |
| Total Height of exhaust rain cap (D) | 1,995 mm |
| Max. Projection of open end door (E) | 850 mm |
| Max. Projection of open side doors (F) | 985 mm |


WEIGHT*

| | |
|---------------------------------|----------|
| Wet (with lube oil and coolant) | 2,896 kg |
|---------------------------------|----------|

SOUND LEVELS*

| Load | 15m | 7m | 1m |
|------|----------|----------|----------|
| 100% | 66 dB(A) | 72 dB(A) | 81 dB(A) |
| 75% | 65 dB(A) | 71 dB(A) | 80 dB(A) |

‡ Bundled fuel tank capacity reduced to 310 litres



FEATURES*

| FEATURES* | Manual Start, Main Power Set | | Automatic Start, Standby Set | |
|---|------------------------------|----------|------------------------------|----------|
| | Standard | Optional | Standard | Optional |
| Sound Attenuated, Weatherproof Canopy | ✓ | | ✓ | |
| Base Fuel Tank | ✓ | | ✓ | |
| DEFRA Bundled Base Fuel Tank (Standard on UK Models)‡ | | ✓ | | ✓ |
| Oil, Fuel & Air Filters | ✓ | | ✓ | |
| Coolant Water Heater | | | ✓ | |
| Lube Oil Pump / Drain | ✓ | | ✓ | |
| Vibration isolated Control Panel | ✓ | | ✓ | |
| Manual Control Panel | ✓ | | | |
| Auto Start Control Panel | | | ✓ | |
| Integral 5A Battery Charger | | | ✓ | |
| Automatic Transfer Panel | | | | ✓ |
| 12 Months International Warranty | ✓ | | ✓ | |
| Output Circuit Breaker | ✓ | | ✓ | |
| CE Certification (Standard on UK/ EU Models) | | ✓ | | ✓ |
| Service / Maintenance Contracts | | ✓ | | ✓ |

*Specifications subject to change without notice

Unit F, Venture Business Park, Witty Street, Hull, East Yorkshire, HU3 4EL, UK

T: +44 (0) 845 430 9110, F: +44 (0) 1482 222646, E: info@jspower.co.uk, W: www.jspower.co.uk